GENERAL SPECIFICATIONS

Performance	 											20 00						 040	
Weights	 							20 10	20 12	20 0	19		10 20 E	0 SE		7798		1000	19
Power Plant																		841	
Fuel and Oil																			34
Baggage	 	ā			* 1											•		.038	
Dimensions						•		•	•0 0•	*: ::		• 50	• •			70.00 /		 846	
Landing Gear	1 . *2 1*3																		
	10.																		

GENERAL SPECIFICATIONS

PERFORMANCE

Published figures are for standard airplanes flown at gross weight under standard conditions at sea level, unless otherwise stated. Performance for a specific airplane may vary from published figures depending upon the equipment installed, the condition of engine, airplane and equipment, atmospheric conditions and piloting technique. Each performance figure below is subject to the same conditions as on the corresponding performance chart from which it is taken in the Performance Charts Section.

Takeoff Ground Run, 25° flaps, sea level (ft)	720
Takeoff Distance Over 50-ft Obstacle, 25° flaps, sea level (ft)	1625
Best Rate of Climb Speed (mph)	85
Rate of Climb (ft per min)	725
Best Angle of Climb Speed, sea level (mph)	76
Max Speed, sea level (mph)	148*
Max Speed Optimum Altitude 9300 ft, 75% power (TAS) (mph)	141*
Service Ceiling (ft)	14,150
Absolute Ceiling (ft)	16,500
Cruise Speed at best power mixture (mph)	
65% power, 12,800 ft	132*
60% power, 14,000 ft	125*
Range at best power mixture (mi)**	
75% power, 9300 ft	645
65% power, 12,800 ft	705
Cruise speed at best economy mixture (mph)	
75% power, 9300 ft	131*
65% power, 12,600 ft	123*
Range at best economy mixture (mi)**	
75% power, 9300 ft	715
65% power, 12,600 ft	774
Stalling Speed, flaps down (CAS) (mph)	61
Stalling Speed, flaps up (CAS) (mph)	68
Landing Roll, sea level, flaps down (ft)	635
Landing Distance Over 50-ft Obstacle, sea level (ft)	1185

^{*}All speeds stated are with optional wheel fairings installed. Subtract 3 mph if wheel fairings are not installed.

WEIGHTS

Gross Weight (lbs)	2450
Standard Empty Weight (lbs)	1404
Maximum Useful Load (lbs)	1046

GENERAL SPECIFICATIONS REVISED: NOVEMBER 21, 1975

1-1

^{**}No reserve.

POWER PLANT		
Engine (Lycoming) Rated Horsepower Rated Speed (rpm) Bore (inches) Stroke (inches) Displacement (cubic Compression Ratio Dry Weight (pounds) Propeller		O-360-A4A or O-360-A4M 180 2700 5.125 4.375 361.0 8.5:1 285 76EM8S5-0-60
FUEL		
AVGAS ONLY		
Fuel Capacity (U.S. § Fuel, Aviation Grade		48 100/130
OIL	W The state of the	
Oil Capacity (qts)		8
BAGGAGE		
Maximum Baggage (Baggage Space (cubic Baggage Door Size (i	ft)	200 24 20 x 22
DIMENSIONS		
Wing Span (ft) Wing Area (sq ft) Wing Loading (lbs po Length (ft) Height (ft) Power Loading (lbs p		32 170 14.4 24.0 7.8 13.6
LANDING GEAR		
Wheel Base (ft) Wheel Tread (ft) Tire Pressure (psi)	Nose	6.7 10 24
Tire Size	Main Nose (4 ply rating) Main (4 ply rating)	24 6.00 x 6 6.00 x 6

